

Proficiency Test

TH-Humidity Transmitter

Many laboratories participate in Proficiency Tests (PT schemes) or interlaboratory comparisons (ILC). Measurement results from multiple laboratories are anonymously compared with each other to identify any deviations. The results will give you valuable insights into your laboratory's performance, ensure and even increase your quality, can be used as a reliable tool for quality and risk management and will meet the requirements of various accreditations and ISO/IEC 17025:2017.

VSL organizes PTs under the ISO/IEC 17043:2023 accreditation with the highest care. When organizing any PT, VSL will:

- provide a suitable artifact;
- compose a test protocol;
- · deliver an independent assessment report;
- provide anonymous comparison of results;
- offer metrological and quality management support at request.

Selection of participants:

Laboratories that measure temperature and relative humidity.

Registration:

Please go to our website <u>www.vsl.nl/en/services/proficiency-testing</u> to fill in the registration form.

Fee:

€ 2.395,00 excluding VAT

The participation fee is including shipping cost for the artifacts.

Terms of payment:

Payment in advance. Invoice will be send 1 month before the start of the PT. Payment is due within 30 days after invoice date.

Schedule:

The PT round is scheduled to begin November 1, 2023. Registration is possible until October 1, 2023.

Estimated number of participants:

Minimal 5 participants.

If the number of participants remains smaller than the minimum number of participants, VSL reserves the right to cancel this PT and will contact the registered participants to offer an alternative.

Reference laboratory:

The reference values for this PT will be delivered by VSL, the National Metrology Institute for The Netherlands.

About VSL

VSL, the National Metrology Institute for The Netherlands, is a globally accredited PT provider (ISO/IEC 17043:2010, our scope reg. nr. R006).

Our independent comparisons covers a broad range of areas including pressure, mass, viscosity, temperature, electricity, length, chemical analysis, humidity and gas flow. Customers also ask VSL for advice and implementation of custom comparisons. We encompass all calibration capabilities across various technological fields listed in our extensive ISO/IEC 17025:2017 accredited calibration scope (reg.nr. K999) and our ISO 17034:2016 scope (reg. nr. P002).







For more information on VSL and our offerings, please visit our website at www.vsl.nl/en/services/proficiency-testing
Should you have any questions or wish to join our PTs, feel free to contact us.





Measurements protocol:

VSL will provide the protocol with the shipment of the artifacts. Each participant will have 2 weeks to perform the calibration.

Evaluation:

Evaluation: Evaluation will be done by normalised error, defined as $E_{\rm n} = \frac{x_i - X_{ref,i}}{\sqrt{U_{ref,i}^2 + U_{stat,i}^2}}$

Confidentiality statement:

VSL keeps all data regarding the performance of individual participants, or groups of participants, strictly confidential. Data is accordingly protected and stored in areas on networks with restricted access. The relationship between results and the laboratories that submitted them will never be disclosed. Only the laboratory is granted access to its performance through the assigned code number.

Deliverables:

VSL will deliver a test report including the anonymized measurement results of the comparison.

Information about the artifact to be circulated:

Humidity and Temperature transmitter - Vaisala HMT333 with sensor

Calibration points:

Maximum tolerance for measure point is 0.1%

Participants may choose a subset of this range depending on their scope.

Temperature setpoint	10 °C	20 °C	30 °C	40 °C
Setpoint realtive humidity %rh	20 %	20 %	20 %	20 %
	35 %	35 %	35 %	35 %
	50 %	50 %	50 %	50 %
	65 %	65 %	65 %	65 %
	90 %	90 %	90 %	90 %

VSL

Thijsseweg 11 2629 JA Delft The Netherlands T +31 (0)15 269 15 00 E vsl@vsl.nl W www.vsl.nl

CoC: 27.228.703 TAX: NL800189620B01 IBAN: NL24ABNA0620273321